

CUTTING FLUID

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

ED HOY'S INTERNATIONAL
27625 DIEHL ROAD
WARRENVILLE, IL. 60555

24 HOUR EMERGENCY
TELEPHONE 1-800-215-4878
INFORMATION ehoy@edhoy.com

PRODUCT NAME LOW ODOR CUTTING FLUID

PRODUCT NUMBERS 5020 -50202-50205
PRODUCT USE GLASS CUTTER LUBRICANT

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid,, colourless, clear

WARNING! COMBUSTIBLE LIQUID AND VAPOR. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF INHALED. PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin contact

Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, burns and other skin damage.

Ingestion

LOW ODOR CUTTING FLUID - 5020

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), Blistering, Lung irritation, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), Lack of coordination, confusion, irregular heartbeat, narcosis (dazed or sluggish feeling), Convulsions, coma

Target Organs

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal.

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

3. COMPOSITION/INFORMATION ON INGREDIENTS



LOW ODOR CUTTING FLUID - 5020

Hazardous Components	CAS-No.	Concentration
SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC	64742-96-7	<=100%

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Foam, Carbon dioxide (CO₂), Dry chemical

LOW ODOR CUTTING FLUID - 5020

Hazardous combustion products

Aldehydes, Hydrocarbons, carbon dioxide and carbon monoxide

Precautions for fire-fighting

If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning liquid with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIA

6. ACCIDENTAL RELEASE MEASURES.

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks).

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a sufficiently high level, sparks can form that may ignite the vapors of flammable liquids. Warning. Sudden release of hot

LOW ODOR CUTTING FLUID - 5020

organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Storage

Store in a cool, dry, ventilated area away from sources of heat, moisture, and incompatible substances.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Eye protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin and body protection

Wear resistant gloves (consult your safety equipment supplier).
To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

LOW ODOR CUTTING FLUID - 5020

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	colourlessclear, colourless
Odour	oilhydrocarbon-like
Boiling point/boiling range	179.00 - 213.90 °C (+/- 81) 460.00 °F @ 760.00 mmHg
Melting point/range	-45 °F / -43 °C
pH	No data
Flash point	176.00 °F Tag closed cup
Evaporation rate	< 0.1 (n-Butyl Acetate)
Lower explosion limit/Upper explosion limit	0.7 %(V) / 6 %(V)
Vapour pressure	0.010 mmHg @ 20 °C
Vapour density	(>) 1 (AIR=1)
Density	0.821 g/cm ³ @ 68 °F / 20 °C 6.7 lb/gal @ 60.1 °F / 15.6 °C
Solubility	negligible in water
Partition coefficient: n-octanol/water	No data
log Pow	no data available
Autoignition temperature	455 - 599 °F / 235 - 315 °C 420 °F / 216 °C

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid

Heat, flames and sparks.

Incompatible products

Chlorine, Strong oxidizing agents, hypochlorites

Hazardous decomposition products

Aldehydes, Hydrocarbons, carbon dioxide and carbon monoxide

Hazardous reactions

Product will not undergo hazardous polymerization.

LOW ODOR CUTTING FLUID - 5020

Thermal decomposition
No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : LD 50 Rat: > 5 g/kg
Acute inhalation toxicity : LC 50 Rat: > 5 mg/l, 4 h
Acute dermal toxicity : LD 50 Rat: > 2,000 mg/kg

12. ECOLOGICAL INFORMATION

Biodegradability
SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available

Bioaccumulation
SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available

Ecotoxicity effects

Toxicity to fish
SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available

Toxicity to daphnia and other aquatic invertebrates.
SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available

Toxicity to algae
SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available

Toxicity to bacteria
SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available



LOW ODOR CUTTING FLUID - 5020

Biochemical Oxygen Demand (BOD)

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available

Chemical Oxygen Demand (COD)

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available

Additional ecological information

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC : no data available

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT /LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	-----------------------------

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS



LOW ODOR CUTTING FLUID - 5020

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - ROAD

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

SARA Hazard Classification

Fire Hazard

Acute Health Hazard

New Jersey RTK Label Information

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC

64742-96-7

Pennsylvania RTK Label Information

SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC

64742-96-7

LOW ODOR CUTTING FLUID - 5020

Notification status

Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	y (positive listing)
China. Inventory of Existing Chemical Substances	y (positive listing)
EU. EINECS	y (positive listing)
Korea. Toxic Chemical Control Law (TCCL) List	y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	y (positive listing)
US. Toxic Substances Control Act	y (positive listing)
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	y (positive listing)
Japan. Kashin-Hou Law List	y (positive listing)

	HMIS	NFPA
Health	1	1
Flammability	2	2
Physical hazards	0	
Instability		0
Specific Hazard	--	--

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.