

**MSDS - Pros Putty.xlsx**

Tuesday, November 23, 2010 8:05 AM

**From:** "Margarette Magruder" <mmagruder@edhoy.com>  
**To:** "Julie Leuck" <julieleuck@yahoo.com>

MSDS sheets for 52012,52010,52011,520103,520102,520112

<h1>Material Safety Data Sheet</h1>	<b>24 Hour Emergency Phone Numbers:</b> 812-952-1649 or 502-541-4214																																																										
	NOTE: National Response Center emergency numbers are to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.																																																										
<p>IMPORTANT: Provide this information to employees, customers, and users of this product. Read this MSDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.</p>																																																											
<p>This Material Safety Data Sheet is available in French, Spanish and German upon request.          Cette fiche signalétique est disponible en français canadien, espagnol hispanique américain et allemand sur demande.          Esta hoja de seguridad está disponible en francés canadiense, español hispano americanos y alemanes bajo petición.          Das Sicherheitsdatenblatt ist erhältlich in Kanadisches Französisch, spanisch, amerikanisch Spanisch und Deutsch auf Anfrage.</p>																																																											
<b>SECTION 1 - Chemical Product / Company Information</b>																																																											
<table border="0" style="width: 100%;"> <tr> <td style="width: 20%;">Product Name:</td> <td style="width: 40%;">Pro's Putty</td> <td style="width: 20%;">Revision Date:</td> <td style="width: 20%;">11/2010</td> </tr> <tr> <td>Product Use</td> <td>Solvent Based Glazing</td> <td>Supercedes:</td> <td>Jan-98</td> </tr> <tr> <td>Manufactur</td> <td>RT Industries</td> <td>MSDS Number:</td> <td>10402010</td> </tr> <tr> <td></td> <td colspan="3">8677 Heinze Road NE Lanesville, IN 47136 812-952-1649 (non-emergency)</td> </tr> </table>		Product Name:	Pro's Putty	Revision Date:	11/2010	Product Use	Solvent Based Glazing	Supercedes:	Jan-98	Manufactur	RT Industries	MSDS Number:	10402010		8677 Heinze Road NE Lanesville, IN 47136 812-952-1649 (non-emergency)																																												
Product Name:	Pro's Putty	Revision Date:	11/2010																																																								
Product Use	Solvent Based Glazing	Supercedes:	Jan-98																																																								
Manufactur	RT Industries	MSDS Number:	10402010																																																								
	8677 Heinze Road NE Lanesville, IN 47136 812-952-1649 (non-emergency)																																																										
<b>SECTION 2 - Composition / Information On Ingredients</b>																																																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Chemical Name</th> <th>CASRN</th> <th>WT%</th> <th>ACGIH TWA</th> <th>ACGIH STEL</th> <th>ACGIH CEIL</th> <th>OSHA TWA</th> <th>OSHA STEL</th> <th>OSHA CEIL</th> <th>Skin</th> </tr> </thead> <tbody> <tr> <td>Calcium Carbonate</td> <td>1317-65-3</td> <td>60-100</td> <td>10 MGM3</td> <td>N.E.</td> <td>N.E.</td> <td>5MGM3</td> <td>N.E.</td> <td>N.E.</td> <td>No</td> </tr> <tr> <td>Talc, non-fibrous</td> <td>148-96-6</td> <td>5-10</td> <td>2MGM3</td> <td>N.E.</td> <td>N.E.</td> <td>N.E.</td> <td>N.E.</td> <td>N.E.</td> <td>No</td> </tr> <tr> <td>Stoddard Solvent</td> <td>8052-41-3</td> <td>1-5</td> <td>100 PPM</td> <td>N.E.</td> <td>N.E.</td> <td>500 PPM</td> <td>N.E.</td> <td>N.E.</td> <td>No</td> </tr> <tr> <td>Silica, Crystalline</td> <td>14808-60-7</td> <td>0.1-1.0</td> <td>0.05MGM3</td> <td>N.E.</td> <td>N.E.</td> <td>(10/% Sio 2)/2MGM3</td> <td>N.E.</td> <td>N.E.</td> <td>No</td> </tr> </tbody> </table>										Chemical Name	CASRN	WT%	ACGIH TWA	ACGIH STEL	ACGIH CEIL	OSHA TWA	OSHA STEL	OSHA CEIL	Skin	Calcium Carbonate	1317-65-3	60-100	10 MGM3	N.E.	N.E.	5MGM3	N.E.	N.E.	No	Talc, non-fibrous	148-96-6	5-10	2MGM3	N.E.	N.E.	N.E.	N.E.	N.E.	No	Stoddard Solvent	8052-41-3	1-5	100 PPM	N.E.	N.E.	500 PPM	N.E.	N.E.	No	Silica, Crystalline	14808-60-7	0.1-1.0	0.05MGM3	N.E.	N.E.	(10/% Sio 2)/2MGM3	N.E.	N.E.	No
Chemical Name	CASRN	WT%	ACGIH TWA	ACGIH STEL	ACGIH CEIL	OSHA TWA	OSHA STEL	OSHA CEIL	Skin																																																		
Calcium Carbonate	1317-65-3	60-100	10 MGM3	N.E.	N.E.	5MGM3	N.E.	N.E.	No																																																		
Talc, non-fibrous	148-96-6	5-10	2MGM3	N.E.	N.E.	N.E.	N.E.	N.E.	No																																																		
Stoddard Solvent	8052-41-3	1-5	100 PPM	N.E.	N.E.	500 PPM	N.E.	N.E.	No																																																		
Silica, Crystalline	14808-60-7	0.1-1.0	0.05MGM3	N.E.	N.E.	(10/% Sio 2)/2MGM3	N.E.	N.E.	No																																																		

## Exposure Notes:

CASIN	Exposure N
14807-96-6	The talc (CAS number 14807-96-6) within this product naturally contains a non-fibrous tremolite (CAS number 14567-73-8), non-fibrous serpentine (CAS number 12135-86-3), and non-fibrous

anthophyllite (CAS number 17068-78-9). Refer to 29 CFR 1910.1000 Table Z 3 for the permissible exposure limits associated with non-fibrous talc and these naturally occurring incidental constituents.

**Important:** Listed Permissible Exposure Levels (Pel) are from the U.S. Dept. of Labor OSHA Final Rule Limits (CFR 29 1910.1000); these limits may vary between states.

**Note:** An employee's skin exposure to substances having a "YES" in the "SKIN" column in the table above shall be prevented or reduced to the extent necessary under the circumstances through the use of gloves, goggles or other appropriate personal protective equipment, engineering controls or work practices.

### SECTION 3 - Hazards Identification

**Emergency Overview:** A gray paste with a little or no odor. **WARNING!** Harmful if swallowed or absorbed through the skin. Combustible liquid and vapro. Aspiration hazard if swallowed - can enter lungs and cause damage. Vapors harmful if inhaled. May cause eye, skin, nose, throat and respiratory tract irritation.

Refer to other MSDS sections for other detailed information.

**Effects of Exposure - Eye Contact:** May cause eye irritation.

**Effects of Exposure - Skin Contact:** Harmful if absorbed through the skin. May cause skin irritation.

**Effects of Exposure - Inhalation:** Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes). Inhalation of high vapor concentrations can cause CNS-depression and narcosis. Dust from dry sanding may cause eye, skin, nose, throat and respiratory tract irritation. Harmful if inhaled, may affect the brain or nervous system causing dizziness, headache or nausea.

**Effects of Exposure - Ingestion:** Harmful if swallowed. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis, which can be fatal. If ingested, may cause vomiting, diarrhea, and depressed respiration.

**Effects of Exposure - Chronic Hazards:** Prolonged and repeated skin contact may cause irritation and possibly dermatitis. Repeated or prolonged exposure may cause respiratory system damage. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Symptoms include: loss of memory, loss of intellectual ability and loss of coordination.

**Primary Route(s) of Entry:** Skin contact, skin absorption, inhalation.

**Medical Conditions which may be aggravated by exposure:** None known.

### SECTION 4 - First Aid Measures

**First Aid - Eye Contact:** In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

**First Aid - Skin Contact:** Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if symptoms persist. Remove and wash contaminated clothing.

**First Aid - Inhalation:** If inhaled, remove to fresh air. If breathing is difficult, leave the area to obtain fresh air. If continued breathing difficulty is experienced, get medical attention immediately.

**First Aid - Ingestion:** If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately. Harmful or fatal if liquid is aspirated into lungs. If swallowed, drink 8-10 oz. of water, get immediate medical attention.

**Note to Physician:** No information.

**COMMENTS:** Call Medical Emergency at 1-800-327-3874 if any irritation or complication arise from any of the above routes of entry.

<b>SECTION 5 - Fire Fighting Measures</b>

**Flash Point, F:** >194

**Lower Explosive Limit, %:** Not Established

**Method:** (Seta Closed Cup)

**Upper Explosive Limit, %:** Not Established

**Extinguishing Media:** Carbon Dioxide, Dry Chemical, Foam

**Unusual Fire and Explosion Hazards:** Store away from caustics and oxidizers. Containers may explode if exposed to extreme heat. Eliminate sources of ignition; heat, electrical equipment, sparks and flames. Combustible liquid. At elevated temperatures, vapors can form an ignitable mixture with air. Vapors can flow along surfaces to distant ignition sources and flash back.

**Special Firefighting Procedures:** Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

<b>SECTION 6 - Accidental Release Measures</b>

**Steps to be Taken if Material is Released or Spilled:** Wear proper protective equipment as specified in Section 8. Immediately eliminate sources of ignition. Use absorbent material or scrape up dried material and place in container.

<b>SECTION 7 - Handling and Storage</b>

**Handling:** KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Avoid contact with skin and eyes. Use in well ventilated area. Avoid breathing vapor and contact with eyes, skin and clothing. Open all windows and doors or use other means to ensure cross-ventilation and fresh air entry during application and drying. Odor is not an adequate warning for hazardous conditions. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal. Wash thoroughly after handling.

**Storage:** Close container after each use. Store containers away from excessive heat and freezing. Keep containers tightly closed. Keep away from heat and sources of ignition. Store away from caustics and oxidizers. Do not store at temperatures above 120 degrees F.

<b>SECTION 8 - Exposure Controls / Personal Protection</b>
--

**Precautionary Measures:** Please refer to other sections and subsections of this MSDS.

**Engineering Controls:** Provide sufficient general and/or local exhaust ventilation to maintain exposure below recommended exposure limit. Good general ventilation should be sufficient to control airborne levels. Vapors are heavier than air and may spread along floors.

**Respiratory Protection:** A NIOSH-approved air purifying respirator with an organic vapor cartridge or canister may be necessary under certain circumstances where airborne concentrations are expected to exceed exposure limits. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear and appropriate, properly fitted respirator (NIOSH approved) during and after application.

**Skin Protection:** Impervious gloves.

**Eye Protection:** Goggles or safety glasses with side shields.

**Other Protective Equipment:** Provide eyewash and solvent impervious apron if body contact may occur.

**Hygienic Practices:** Remove and wash contaminated clothing before re-use. Wash hands before breaks and at the end of the workday. Do not smoke.

<b>SECTION 9 - Physical and Chemical Properties</b>
---

<b>Boiling Range:</b>	325 - 340 F	<b>Vapor Density:</b>	Not Established
<b>Odor:</b>	Little or None	<b>Odor Threshold:</b>	Not Established
<b>Appearance:</b>	Gray	<b>Evaporation Rate:</b>	Slower than n-Butyl Acetate
<b>Solubility in H<sup>2</sup>O:</b>	Not Established	<b>Specific Gravity:</b>	2.149
<b>Freeze Point:</b>	Not Established	<b>pH:</b>	Not Established
<b>Vapor Pressure:</b>	Not Established	<b>Viscosity:</b>	Not Established
<b>Physical State:</b>	Paste		

When reported, vapor pressure of this product has been calculated theoretically based on its constituent makeup and has not been determined experimentally.

(See section 16 for abbreviation legend.)

<b>SECTION 10 - Stability and Reactivity</b>
--

**Conditions to Avoid:** Excessive heat and freezing.

**Incompatibility:** Incompatible with strong bases and oxidizing agents.

**Hazardous Polymerization:** Hazardous polymerization will not occur under normal conditions.

**Stability:** Stable under recommended storage conditions.

<b>SECTION 11 - Toxicological Information</b>
---

**Product LD50:** Not Established

**Product LC50:** Not Established

**Carcinogenicity:**

CAS No.	Chemical	ACGIH	OSHA	IARC	NTP	WT%
14808-60-7	Silica, cryst	Suspecte	--	--	Known carcinogen	0.1-1.0

**Significant Data with Possible Relevance to Humans:** None.

<b>SECTION 12 - Ecological Information</b>
--

**Ecological Information:** Ecological injuries are not known or expected under normal use.

**Ecological Information:** Ecological injuries are not known or expected under normal use.

<b>SECTION 13 - Disposal Information</b>
--

**Disposal Information:** Disposal of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

**EPA Waste Code if Discarded (40 CFR Section 261):** This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261.

<b>SECTION 14 - Transportation Information</b>
--

**DOT Proper Shipping**

**Packing Group:**

N.A.



Chemical			CAS Nu		WT%
Non-Hazard			Proprietar		3-7
Butene, ho			Proprietar		3-7

**California Proposition 65:**

WARNING: he following ingredients present in the product are known to the State of California to cause cancer:

Chemical		CAS Nu		Definition		Date List			WT%
Silica, crysta		14808-60		Carcinoge		Listed: Oc			0.1-1.0

WARNING: The following ingredients present in the product are known to the State of California to cause birth defects or other reproductive harm:

<b>SECTION 16 - Other Information</b>									
---------------------------------------	--	--	--	--	--	--	--	--	--

**HMIS Ratings:**

Health: 1                      Flammability: 1                      Reactivity: 0                      Personal Protection: X

**Volatile Organic Compounds:** GR/LTR: 47.5                      LB/GAL: 0.4                      WT%: 2.215

**Reason for Revision:** Periodic Update

<b>Legend:</b>	N.A. - Not Applicable	ACGIH - American Conference of Governmental Industrial Hygienists
	N.E. - Not Established	SARA - Superfund Amendments and Reauthorization Act of 1986
	N.D. - Not Determined	NJRTK - New Jersey Right-to-Know Law
	VOC - Volatile Organic Compound	OSHA - Occupational Safety and Health Administration
	PEL - Permissible Exposure Limit	HMIS - Hazardous Materials Identification System
	TLV - Threshold Limit Value	NTP - National Toxicology Program
	STEL - Short Term Exposure Limit	CEIL - Ceiling Exposure Limit
	LD50 - Lethal Dose 50	LC50 - Lethal Concentration 50
	F - Degree Fahrenheit	CASRN - The Chemical Abstracts Service Registry Number
	MSDS - Material Safety Data Sheet	
	C - Degree Celcius	

RT Industries believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determined if they are appropriate.

<end of MSDS>

